

Power where you need it.®



Product Summary

Model	Power Specification @ 20°C	Fuel Consumption at Full Power *All natural Gas is Std. 1000 BTU/SCF 37.7 MJ/Sm ³ gas	Dimensions LxWxH mmxx(inches)	Weight kg (lb)
P-5050	50 Watts @ 6.7 Volts 50 Watts @ 12 Volts 50 Watts @ 24 Volts	Natural Gas: 4.8 m ³ /day (168 ft ³ /day) Propane: 7.2 l/day (1.9 US gal/day) / 3.6 kg/day Max. Supply Pressure: 344 kPa (50 psig) Min. Supply Pressure: 103 kPa (15 psig)	772 x 306 x 991 (30 x 12 x 39)	41 (90)
P-5100	100 Watts @ 6.7 Volts 100 Watts @ 12 Volts 100 Watts @ 24 Volts 100 Watts @ 48 Volts	Natural Gas: 9.9 m ³ /day (350 ft ³ /day) Propane: 15.4 l/day (4.1 US gal/day) / 7.7 kg/day Max. Supply Pressure: 344 kPa (50 psig) Min. Supply Pressure: 103 kPa (15 psig)	790 x 309 x 991 (31 x 12 x 39)	60 (132)
5220	195 Watts @ 12 Volts 178 Watts @ 24 Volts	Natural Gas: 19.7 m ³ /day (700 ft ³ /day) Propane: 28.0 l/day (7.4 US gal/day) / 14.2 kg/day Max. Supply Pressure: 345 kPa (50 psig) Min. Supply Pressure: 165 kPa (24 psig)	810 x 450 x 1275 (31 x 18 x 50)	97 (214)
S-8500	460 Watts @ 12 Volts 520 Watts @ 24 Volts 460 Watts @ 48 Volts	Natural Gas: 50.4 m ³ /day (1780 ft ³ /day) Propane: 76 l/day (20.1 US gal/day) / 38 kg/day Max Supply Pressure: 344 kPa (50 psig) Min. Supply Pressure: NG: 103 kPa (15 psig) LPG: 166 kPa (24psig)	941 x 941 x 2468 (37 x 37 x 97)	274 (604)
1500 <small>Hazardous Approved (Class 1, Div. 2)</small>	500 Watts @ 24 Volts	Natural Gas: 48.0 m ³ /day (1695 ft ³ /day) Propane: N/A Max Supply Pressure: 172 kPa (25 psig) Min. Supply Pressure: 103 kPa (15 psig)	1416 x 1416 x 2899 (56 x 56 x 114)	700 (1530)

Specification sheets are subject to change – To verify that you have the most current information, please contact a Gentherm Global Power Technologies Representative.

***Custom Configuration** – Please contact a Gentherm Global Power Technologies Representative.

